REST API - Fields Configuration

[Alkaes JIRA Plugin Field Administration Enhanced](#) provides some additional capabilities related modification of Field Configuration.

Hide in Others

Goal : Allows to hide some _Fields_ from all others Field Configuration excepted a part of them.

Usage : As soon as you had a new Customfield your JIRA instance, it is added systematically in all Field Configuration. This default behaviour is not the most expected one. In practice, if this field has a default value (it is more frequent for types **_Select_**, **Radiobutton** and **_Checkbox_**), this value willbe store in database, even if it has no sense for the most of Issue Type managed in your JIRA instance.

By using this APIs, you can remove/hide the concerned Field in all other Field Configuration.

API	/rest/extendedAdmin/1.0/fields/hideInOthers
Method	POST

Payload	**_Schema_**
	
	 <table><tr><th>Property</th><th>Value</th><th>Description</th></tr><tr><td>fieldLayoutId</td><td>Long</td><td>Id of FieldLayout (Field Configuration) where the identified Fields have to be kept.</td></tr><tr><td>fieldLayoutIds</td><td>List<Long></td><td>List of Ids of FieldLayouts (Field Configurations) where the identified Fields have to be kept.</td></tr><tr><td>fieldIds</td><td>List<String></td><td>List of Ids of Custom Fields that have to be kept in identified FieldLayout(s)</td></tr></table> **_Samples_**
	
	 `{"fieldLayoutIds":["10200","10201"],"fieldIds":["customfield_10400"]}`
	
	 `{"fieldLayoutIds":["10200"],"fieldIds":["customfield_10400"]}`
	
	 `{"fieldLayoutId":10200,"fieldIds":["customfield_10400"]}`

Return Code	**200** : All changes performed without issue. **500** : Changes failed.
Return	There is no special return provided, since this request can meet some Timeout. All needed details are traced in log files

Hide Field in Other

Goal : Allows to hide some _Field_ from all others Field Configurations excepted the current.

Usage : See above.

API	/rest/extendedAdmin/1.0/fields/hideFieldInOther
Method	GET
Parameters	<table><tr><th>Property</th><th>Value</th><th>Description</th></tr><tr><td>fieldLayoutId</td><td>Long</td><td>Id of FieldLayout (Field Configuration) where the identified Fields have to be kept.</td></tr><tr><td>fieldId</td><td>String</td><td>Id of Custom Fields that have to be kept in identified FieldLayout(s)</td></tr></table>
Return Code	**200** : All changes performed without issue. **500** : Changes failed.

Return	Not yet documented ...

Hide All

Goal : Allows to hide all *Fields* from the current Field Configuration.

Usage : To crearte a new Field Configuration, you can :

- Create a new one from scratch. It will include all fields
- Copy from another one. It will include the same fields

In most of cases, you should not need all of these fields.

API	/rest/extendedAdmin/1.0/fields/hideAll		
Method	GET		
Parameters	**Property**	**Value**	**Description**
	fieldLayoutId	Long	Id of FieldLayout (Field Configuration) where the identified Fields have to be kept.
Return Code	200	: All changes performed without issue.	
	500	: Changes failed.	
Return	Not yet documented ...		