

Extending Workflow Attributes Editor

Overview

As Plugins Developer, you will find here, some details on how to implement your own Meta-Attribute Editor dedicated to your custom Meta-Attribute.

How to extend Meta-Attributes Editors

To append a new Meta-Attributes Editors, you will have to process as follow ...

- Create a Velocity template providing the Attribute Editor

See below the Boolean editor

```
<td class="fieldLabelArea">$i18n.getText("minyaa.workflows.attribute.  
booleanValue")</td>  
<td class="fieldValueArea">  
    <input type="radio" name="metaAttributeBooleanValue" id="  
attributeRadioValue1" size="30" value="true" />  
    <label for="attributeRadioValue1"> $i18n.getText("admin.  
common.words.true")</label>  
    <input type="radio" name="metaAttributeBooleanValue" id="  
attributeRadioValue2" size="30" value="false" />  
    <label for="attributeRadioValue2"> $i18n.getText("admin.  
common.words.false")</label>  
    <br />  
</td>
```

- Create a Javascript applying the edited value into the Input field.

... always for Boolean editor

```
jQuery(document).ready(function(){  
    MYAAWA.namespace("MYAAWA.Editors.editMetaBoolean");  
    MYAAWA.Editors.editMetaBoolean.init = function(inputValue) {  
        var editedValue =  
AJS.$("[name='metaAttributeBooleanValue']");  
        var onChanged = function(event) {  
            inputValue.val(event.target.value);  
        };  
        MYAAWA.Editors.editMetaBoolean.onChanged = onChanged;  
        editedValue.change(MYAAWA.Editors.editMetaBoolean.  
onChanged);  
    };  
});
```

- Define a Web Resource for this JS file. It has to be in dependency with MYAA_WorkflowsAttribute.js

... again for Boolean editor

```
<web-resource key="MYAA_editMetaBoolean" name="MYAA-editMetaBoolean">  
    <dependency>jira.plugin.minyaa.workflows.attributes:  
MYAA_WorkflowsAttributes</dependency>  
    <resource type="download" name="editMetaBoolean.js"  
location="com/minyaa/workflows/js/MYAA.editMetaBoolean.js">  
        <property key="content-type" value="text/javascript"  
/>  
    </resource>  
    <context>atl.admin</context>  
</web-resource>
```

On this page:

- [Overview](#)
- [How to extend Meta-Attributes Editors](#)
- [How to extend Meta-Attributes](#)

- and finally, defined the meta-editor, specifying the related Velocity template

... a last one for Boolean editor

```
<meta-editor key="editMetaBoolean" name="Edit Meta Attribute as
Boolean">
    <resource type="velocity" name="edit" location="com/minyaa
/workflows/templates/meta-attributes-edit-boolean.vm"/>
</meta-editor>
```

How to extend Meta-Attributes

To extend the list of displayed Meta-Attributes depending on the list of supported process as follow ...
Use the custom plugin module-type meta-attribute

```
<meta-attribute key="sampleAttribute" name="sample.attribute" isUnique="
false" valueEditorKey="jira.plugin.minyaa.workflows.attributes:
editMetaBoolean" >
    <description key="sample.attribute.desc">Do nothing !.<
/description>
    <scope
        initialAction="true"
        globalAction="true"
        commonAction="true"
        stepAction="true"
        initialStep="true"
        normalStep="true"
        finalStep="true"
    />
</meta-attribute>
```

Where ...

- **isUnique** specifies if the attribute may be use more than one time by Step of Transition (*Not yet completely supported*).
- **valueEditorKey** specifies the editor to use. Use the complete key.
- **scope** specifies if the attribute can be use as Step Meta-Attribute or Transition Meta-Attribute

Different types of Step and Action are possible, but will managed only by Minyaa Workflows Designer

Meta-Attributes may be also added through a Plugin Component. The Component will have to implement the interface **MetaAttributesProvider** as follow ...

```

public class YourMetaAttributesProvider implements MetaAttributesProvider {

    private MetaAttributeManager metaAttributeManager;

    public WorkflowMetaAttributesProvider(MetaAttributeManager
metaAttributeManager) {
        this.metaAttributeManager = metaAttributeManager;
        metaAttributeManager.addMetaAttributesProvider(this);
    }

    public void refresh() {
        MetaAttributeModule metaAttributeModule;

        metaAttributeModule = new MetaAttributeModule("sample.step.
attribute");
        metaAttributeModule.appendDescription("Do nothing
special").appendScopes(metaAttributeManager.getAllAvailableStepScopes());
        metaAttributeModule.appendValueEditorKey("jira.plugin.
minyaa.workflows.attributes:editMetaBoolean");
        metaAttributeManager.addMetaAttributes
(metaAttributeModule);

        metaAttributeModule = new MetaAttributeModule("new.boolean.
action.attribute");
        metaAttributeModule
            .appendDescription("Define if it is True or False
!!!")
            .appendScopes(metaAttributeManager.
getAllAvailableActionScopes());
        metaAttributeModule.appendValueEditorKey
(MetaAttributeManager.META_VALUE_EDITOR_BOOLEAN_KEY);
        metaAttributeManager.addMetaAttributes
(metaAttributeModule);
    }
}

```